Material Safety Data Sheet



STONEMEDIC GPC GRANITE POLISHING CREAM

Section 1. Chemical product and company identification

Trade name

: STONEMEDIC GPC GRANITE POLISHING CREAM

Product use

Floor care product

Supplier

: Ecolab Inc.

370 N. Wabasha St. St. Paul. MN 55102 1-800-352-5326

Code

: 904005-01

Date of issue

24-September-2008

EMERGENCY HEALTH INFORMATION: 1-800-328-0026 Outside United States and Canada CALL 1-651-222-5352 (in USA)

Section 2. Composition, information on ingredients

Name	CAS number	% by weight
aluminium oxide	1344-28-1	49
tin (iv) oxide	18282-10-5	5 - 20
oleic acid	112-80-1	1 - 5
2-aminoethanol	141-43-5	1 - 5

Section 3. Hazards identification

Physical state

: Liquid. [Liquid.]

Emergency overview

: CAUTION!

MAY CAUSE RESPIRATORY TRACT, EYE AND SKIN IRRITATION.

Avoid contact with eyes, skin and clothing. Avoid breathing vapors, spray or mists. Use only with adequate ventilation. Keep container closed. Wash thoroughly after handling.

Potential acute health effects

Eyes Skin

: Moderately irritating to eyes.

Inhalation

: Moderately irritating to the skin.

: Moderately irritating to the respiratory system.

: No known significant effects or critical hazards. Ingestion

See toxicological information (section 11)

Section 4. First aid measures

Eye contact

: In case of contact, immediately flush eyes with plenty of water. Remove contact lenses and flush again. Get medical attention if irritation persists.

Skin contact

: In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if irritation persists. Wash clothing before reuse. Clean

shoes thoroughly before reuse.

Inhalation

: If inhaled, remove to fresh air.

Ingestion

: Do not induce vomiting. Never give anything by mouth to an unconscious person. If irritation

persists, get medical attention.

Section 5. Fire fighting measures

Flash point

Hazardous thermal decomposition products : Decomposition products may include the following materials:

carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides

Fire-fighting media and

instructions

: Use an extinguishing agent suitable for the surrounding fire.

Dike area of fire to prevent runoff.

In a fire or if heated, a pressure increase will occur and the container may burst. Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure

Special protective equipment :

for fire-fighters

Section 6. Accidental release measures

Personal precautions : Use suitable protective equipment (section 8). Do not allow to enter drains or watercourses.

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution

(sewers, waterways, soil or air).

Methods for cleaning up

: For small spills, add absorbent (soil may be used in the absence of other suitable materials), scoop up material and place in a sealable, liquid-proof container for disposal. For large spills, dike spilled material or otherwise contain it to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal.

Section 7. Handling and storage

Handling

: Avoid contact with eyes, skin and clothing. Avoid breathing vapors, spray or mists. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.

Storage

Keep out of reach of children. Keep container in a cool, well-ventilated area. Keep container tightly closed.

Store between the following temperatures: 0 and 45°C

Section 8. Exposure controls/personal protection

Engineering measures : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Personal protection:

Eyes

: Eye protection recommended.

Hands

: For prolonged or repeated handling, use the following type of gloves: Impervious gloves.

Skin

: No protective equipment is needed under normal use conditions.

Respiratory

: Avoid breathing vapors, spray or mists.

Exposure limits

aluminium oxide

OSHA PEL (United States, 11/2006).

TWA: 5 mg/m3 8 hour(s). Form: Respirable fraction

TWA: 15 mg/m³ 8 hour(s). Form: Total dust

tin (iv) oxide

ACGIH TLV (United States, 1/2008). TWA: 2 mg/m³, (as Sn) 8 hour(s).

2-aminoethanol

ACGIH TLV (United States, 1/2008).

STEL: 15 mg/m3 15 minute(s). STEL: 6 ppm 15 minute(s). TWA: 7.5 mg/m³ 8 hour(s). TWA: 3 ppm 8 hour(s).

OSHA PEL (United States, 11/2006).

STONEMEDIC GPC GRANITE POLISHING CREAM

TWA: 6 mg/m³ 8 hour(s). TWA: 3 ppm 8 hour(s).

Section 9. Physical and chemical properties

Physical state

: Liquid. [Liquid.]

Color

: Gray. [Dark]

Odor

: Floral.

рΗ

: 9.945 [Conc. (% w/w): 100%]

Relative density

Solubility

: Soluble in the following materials: cold water and hot water.

Section 10. Stability and reactivity

Stability

: The product is stable. Under normal conditions of storage and use, hazardous

polymerization will not occur.

Reactivity

: Reactive or incompatible with the following materials: acids.

products

Hazardous decomposition: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

Hazardous polymerization

: Under normal conditions of storage and use, hazardous polymerization will not occur.

Section 11. Toxicological information

Potential acute health effects

: Moderately irritating to eyes. **Eyes** : Moderately irritating to the skin. Skin

: Moderately irritating to the respiratory system. Inhalation : No known significant effects or critical hazards. Ingestion

Potential chronic health effects

Target organs

: Contains material which causes damage to the following organs: kidneys, liver. Contains material which may cause damage to the following organs: lungs, upper respiratory tract, central nervous system (CNS).

Section 12. Ecological information

Section 13. Disposal considerations

Waste disposal

: The generation of waste should be avoided or minimized wherever possible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Consult your local or regional authorities.

Section 14. Transport information

Certain shipping modes or package sizes may have exceptions from the transport regulations. The classification provided may not reflect those exceptions and may not apply to all shipping modes or package sizes.

UN Classification

Not regulated.

See shipping documents for specific transportation information.

Section 15. Regulatory information

HCS Classification : Irritating material

Target organ effects

U.S. Federal regulations : SARA 302/304/311/312 extremely hazardous substances: No products were

found.

SARA 302/304 emergency planning and notification: No products were

found.

TSCA 8(b) inventory : All components are listed or exempted.

SARA 313 Product name
Form R - Reporting requirements: aluminium oxide

<u>CAS number</u> <u>Concentration</u>

1344-28-1 49.5

California Prop. 65

: No products were found.

Section 16. Other information

Hazardous Material

Information System (U.S.A.)

Health * 1
Flammability 0
Physical hazards 0

Date of issue

: 24-September-2008.: Regulatory Affairs: 27-October-2005.

Date of previous issue

Notice to reader

Responsible name

The above information is believed to be correct with respect to the formula used to manufacture the product in the country of origin. As data, standards, and regulations change, and conditions of use and handling are beyond our control, NO WARRANTY, EXPRESS OR IMPLIED, IS MADE AS TO THE COMPLETENESS OR CONTINUING ACCURACY OF THIS INFORMATION.