InnoTops Spec Sheet 2018

Name	I-BRACE 13	I-BRACE 20	UPPER BRACE 10	UPPER BRACE 15	L-BRACE 10	L-BRACE 15
SKU#	12458	12460	12464	12465	12461	12462
Width	2.5"	2.5"	2.5"	2.5"	2.5"	2.5"
Thickness	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"
Length	13"	20"	10"	15"	10"	15"
Weight	1.6 lbs	2.45 lbs	1.66 lbs	2.65 lbs	2.3 lbs	3.15 lbs
Overhangs Supported	6-16" One-level Countertops	12-22" One- level Countertops	12-19" Upper bars* (5.5-12.5" overhangs)	17-24" Upper bars* (10.5-17.5" overhangs)	12-19" Upper bars* (5.5-12.5" overhangs)	17-24" Upper bars* (10.5-17.5" overhangs)
Placement**	16-24" centers	16-24" centers	16" centers	16" centers	16-24" centers	16-24" centers
# Available Anchor Points	8	8	6	6	6	6
# Anchor Points Used	3	3	4	4	4+1	4+1

^{*} Upper bars are overhangs that are supported on a half-wall and differ from one-level breakfast bars.

^{**} Placement depends on the integrity of the stone and support base. If the stone has many fissures or is soft, use more support braces. Fabricators should use their best judgment.